



Product Specification TV4



Industrial Strength Key-fob Tag

Basic features:-

- Hands free reading range (>2.0 m)
- High fidelity reading (1:100 million error rate)
- Secure **digital** data exchanges
- Long life active tag
- Battery low indicator
- Stainless steel attachment point
- Fast multiple (anti-clash) reading
- Inert until in reader detection zones

TV4 Technical Specification:-

Coding:	Variable up to 64 bits	
Physical Size: Teardrop	55 x 42 x 11.5 mm	$2\frac{3}{16} \times 1\frac{5}{8} \times \frac{3}{8}$ in.
Weight:	25 gm	1.0 oz.
Material: Body: Lid:	Light grey polycarbonate moulding Dark grey polycarbonate Moulding	
Temperature Specification:	-20°C to +60°C	-4°F to 140°F
Humidity:	100% Condensing	
Battery Type:	Sealed Lithium CR2430	
Shelf Life:	7 years @ 10°C to 50°C	
Battery Life:	Typically >5 years based on 6 minutes per day.	
Battery Low:	Provides typically 2-3 months notice of demise based on 6 minutes daily use.	
Read Range:	Determined by reader aerial/antenna. Typically >2.0 m Typically >6 ¹ / ₂ ft. Based upon typical single door loop.	
Speed of Reading:	Determined by tag population and tag encoding. Typically 20 per second.	
Disposal:	Return to Identec for safe disposal	

Product specifications are subject to change. Identec reserve the right to modify the design without notice. If any specification is critical to product selection please confirm its availability prior to ordering. E & OE accepted. Issued: April 09.



Identec Ltd. Mercantile Road, Rainton Bridge Ind. Est., Houghton-le-Spring, Co. Durham, England. DH4 5PH. Tel: +44 (0) 191 584 4084, Fax: +44 (0) 191 584 9077. E-mail: info@identec.com, Website: www.identec.com